

L9207-10 / DT4911 Options

DT4280/DT4250 Series (Bundled accessory)



TEST LEAD L9207-10

Cable length 90 cm (2.9527 ft)
with one each red and black caps

with cap
CAT III 1000V/CAT IV 600V
without cap
CAT II 1000V

DT4220 Series (Bundled accessory)




TEST LEAD DT4911

Cable length 54cm (1.77 ft)
with one each red and black caps

with cap
CAT IV 300V/ CAT III 600V
without cap
CAT II 600V

L4933 and L4934 probe tips
(at right) can be used
on L9207-10/DT4911 test leads.



DC70V/AC33V
CONTACT PIN SET L4933



CAT II 600V
CAT III 300V
SMALL ALLIGATOR CLIP SET L4934

L4930 Options

Compatible DMMs: DT4250 Series / DT4280 Series



Length : 1.2m (3.937 ft)
CONNECTION CABLE L4930

Probe tips (at right) can be
used on L4930 connection
cables.



22mm(0.87 in)
φ3.7mm(0.15 in)
with one each red
and black caps
CAT III 600V (with cap)
CAT II 600V (without cap)
TEST PIN SET L4938



CAT III 1000V
CAT IV 600V
ALLIGATOR CLIP SET L4935



30mm
(1.18 in)
CAT III 600V
BUS BAR CLIP SET L4936



Magnet
φ6mm(0.24 in)
CAT III 1000V
MAGNETIC ADAPTER SET L4937




22mm(0.87 in)
φ3.7mm(0.15 in)
48mm(1.89 in)
φ2.6mm(0.15 in)
CAT III 600V
BREAKER PIN L4939



CAT III 1000V /CAT IV 600V
with one each red and black caps
TEST PIN SET L4932



CAT II 1000V
GRABBER CLIP L9243



CAT III 1000V
CAT IV 600V
Length : 1.5m (4.9212 ft)
With coupling connectors
EXTENSION CABLE SET L4931

AC CLAMP ON PROBES for DT4281, DT4253, DT4255, DT4256 (Adapter 9704 required for connection)

Product appearance	 CAT III 600V	 CAT III 600V	 CAT III 600V
Model number	9010-50	9018-50	9132-50
Rated current	AC 10/20/50/100/200/500 A		AC 20/50/100/200/500/1000A
Amplitude accuracy (45 to 66Hz)	±2% rdg. ±1% f.s.	±1.5% rdg. ±0.1% f.s.	±3% rdg. ±0.2% f.s.
Frequency characteristics	40Hz to 1kHz:±6% rdg.	40Hz to 3kHz:±1% rdg.	40Hz to 1kHz:±1% rdg.
Output rate	AC 0.2 V f.s. (For each range)		
Max. circuit voltage	AC600 V (50/60Hz)		
Diameter	φ46mm (1.81 in) or less		φ55mm (2.17 in) or less, 80x20mm (3.15x0.79 in)
Dimensions, mass	78Wx188Hx35D mm (3.07W x 7.40H x 1.38D in) 420g (14.8oz.), cord length 3m (9.84 ft)		100Wx224Hx35D mm (3.94W x 8.82 H x 1.38D in) 600g(21.1oz.), cord length 3m(9.84 ft)

Adapter Model 9704 is required to connect
AC CLAMP ON PROBES 9010-50, 9018-
50 and 9132-50 to the DT4281, DT4253,
DT4255, DT4256.



CONVERSION ADAPTER 9704

Other options



THERMOCOUPLES (K) DT4910

- Thermal junction form: exposed weld
- Sensor length: approx. 800 mm
- Measurement temperature range
-40 to 260°C
- Allowable tolerance:±2.5°C



COMMUNICATION PACKAGE (USB) DT4900-01

- Communication cable
 - Communication adapter
 - PC software
 - Instruction manual
- OS: Windows 8.1/8/7, Vista
(SP1 or later)



**MAGNETIC
STRAP
Z5004**



**MAGNETIC
STRAP
Z5020**



**CARRYING CASE
C0200**
DT4220 Series



**CARRYING CASE
C0202**
DT4250/DT4280 Series



**CARRYING CASE
C0201**
DT4250 Series



**CARRYING CASE
3853**
DT4250 Series

HIOKI
HIOKI E. E. CORPORATION

HEADQUARTERS

81 Koizumi,
Ueda, Nagano 386-1192 Japan
<https://www.hioki.com/>



Scan for all
regional contact
information

Note: Company names and product names appearing in this brochure are trademarks or registered trademarks of various companies.

DISTRIBUTED BY